

## CLAIMS

1. A method for detecting an endpoint during a chemical mechanical polishing (CMP) process, comprising the operations of:

receiving a current reflected spectrum data sample corresponding to a plurality of  
5 spectrums of light reflected from an illuminated portion of a surface of a wafer;

normalizing the current reflected spectrum data sample using a normalization  
reference comprising a first reflected spectrum data sample obtained earlier during the  
CMP process; and

updating the normalization reference using a second reflected spectrum data  
10 sample obtained earlier during the CMP process, wherein the second reflected spectrum  
data sample is obtained after the first reflected spectrum data sample.

2. A method as recited in claim 1, further comprising the operation of  
determining an endpoint based on optical interference occurring in the reflected spectrum  
15 data.

3. A method as recited in claim 1, wherein the first reflected spectrum data  
sample trails the current reflected spectrum data sample by a predetermined trailing  
reference delay.

20

4. A method as recited in claim 3, wherein the trailing reference delay is a number representing an amount of reflectance data samples between the current reflected spectrum data sample and the first reflected spectrum data sample.

5 5. A method as recited in claim 3, further comprising the operation of receiving a new current reflected spectrum data sample corresponding to a plurality of spectrums of light reflected from the illuminated portion of the surface of the wafer at a later time.

10 6. A method as recited in claim 5, wherein the second reflected spectrum data sample trails the new current reflected spectrum data sample by the trailing reference delay.

7. A method as recited in claim 2, wherein the optical interference is a result  
15 of phase differences in light reflected from different layers of the wafer.

8. A method as recited in claim 7, wherein the optical interference occurs when a top metal layer is reduced to a thin metal zone.

9. A method as recited in claim 8, further comprising the operation of determining when oscillations occur in a plot of wave-numbers based on the reflected spectrum data.

5 10. A method as recited in claim 9, wherein the endpoint occurs when the oscillations in the plot of wave-numbers occurs.

11. A method for detecting an endpoint during a chemical mechanical polishing (CMP) process, comprising the operations of:

10 receiving a current reflected spectrum data sample corresponding to a plurality of spectrums of light reflected from an illuminated portion of a surface of a wafer;

selecting a first median reflected spectrum data sample from a first plurality of reflected spectrum data samples obtained earlier during the CMP process;

15 normalizing the current reflected spectrum data sample using a normalization reference comprising the median reflected spectrum data sample; and

updating the normalization reference using a second median reflected spectrum data sample selected from a second plurality of reflected spectrum data samples obtained earlier during the CMP process.

12. A method as recited in claim 11, further comprising the operation of determining an endpoint based on optical interference occurring in the reflected spectrum data.

5 13. A method as recited in claim 11, wherein the first plurality of reflected spectrum data samples comprise three consecutive reflected spectrum data samples obtained earlier during the CMP process.

10 14. A method as recited in claim 13, wherein one of the first plurality of reflected spectrum data samples trails the current reflected spectrum data sample by a predetermined trailing reference delay.

15 15. A method as recited in claim 14, wherein the trailing reference delay is a number representing an amount of reflectance data samples between the current reflected spectrum data sample and one of the first plurality of reflected spectrum data samples.

16. A method for detecting an endpoint during a chemical mechanical polishing process, comprising the operations of:

illuminating a portion of a surface of a wafer with broad band light;

receiving a current reflected spectrum data sample corresponding to a plurality of spectrums of light reflected from the illuminated portion of the surface of the wafer;

normalizing the current reflected spectrum data sample using a normalization reference comprising a first reflected spectrum data sample obtained earlier during the

5 CMP process;

determining an endpoint based on optical interference occurring in the reflected spectrum data; and

updating the normalization reference using a second reflected spectrum data sample obtained earlier during the CMP process, wherein the second reflected spectrum

10 data sample is obtained after the first reflected spectrum data sample.

17. A method as recited in claim 16, wherein the first reflected spectrum data sample trails the current reflected spectrum data sample by a predetermined trailing reference delay.

15

18. A method as recited in claim 17, wherein the trailing reference delay is a number representing an amount of reflectance data samples between the current reflected spectrum data sample and the first reflected spectrum data sample.

19. A method as recited in claim 18, further comprising the operation of receiving a new current reflected spectrum data sample corresponding to a plurality of spectrums of light reflected from the illuminated portion of the surface of the wafer at a later time.

5

20. A method as recited in claim 19, wherein the second reflected spectrum data sample trails the new current reflected spectrum data sample by the trailing reference delay.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995